

## BARRA HUECA 1518

BARRA HUECA SAE - 1518			BARRA HUECA SAE - 1518			BARRA HUECA SAE - 1518		
DIAM EXTERIOR MILIMETROS	DIAM INTERIOR MILIMETROS	KG/MT	DIAM EXTERIOR MILIMETROS	DIAM INTERIOR MILIMETROS	KG/MT	DIAM EXTERIOR MILIMETROS	DIAM INTERIOR MILIMETROS	KG/MT
32	16	4.7	75	60	12.9	132	71	77.5
32	20	3.9	80	40	30.1	132	90	58.6
36	16	6.4	80	50	24.5	132	106	39.3
36	20	5.5	80	63	15.5	140	80	82.6
36	25	4.1	85	45	32.6	140	100	60.4
40	20	8.1	85	55	26.4	140	112	44.7
40	25	6.7	85	67	17.4	150	80	100.7
40	28	5	90	50	35.1	150	106	70.9
45	20	10.8	90	63	26	150	125	43.8
45	25	9.5	90	71	19.4	160	90	109.4
45	28	7.7	95	50	40.8	160	112	82
45	32	6.4	95	67	28.6	160	132	51.9
50	25	12.4	95	75	21.5	170	118	94.2
50	30	10.8	100	56	48.2	170	140	59.2
50	32	9.7	100	71	31.2	180	125	105.4
50	35	8.8	100	80	22.8	180	150	63
50	36	8	106	56	50.6	190	132	117.5
56	28	14.5	106	71	38.8	190	160	67.1
56	36	12.1	106	80	30.5	200	140	128.2
56	40	10.1	112	63	53.7	200	160	91.2
63	32	18.5	112	80	38.7	212	150	141.3
63	40	14.9	112	90	28.2	212	170	101.8
63	50	9.4	118	63	62.3	224	160	154.6
71	36	23.5	118	80	47.3	224	180	122.6
71	45	19	118	90	36.8	236	170	168.7
71	56	12.2	125	71	66.2	236	190	124.3
75	40	25.3	125	90	47.3	250	180	189.6
75	50	19.7	125	100	35.6	250	200	142.7

### TOLERANCIAS ESTIMADAS SAE - 1518

45MM A 100 MM	MAS 2 MM
105MM A 140 MM	MAS 2.5 MM
150MM A 190 MM	MAS 3.5 MM
200 MM A 250 MM	DESDE 4 MM HASTA 6 MM